


8 SOLENOID COILS, WITH STANDARD ELECTRIC CONNECTION TO ISO 4400 / DIN 43650, FOR DC SUPPLY

Standard valves type HD5-ES-* are operated by solenoid that are energized directly from a D.C. voltage supply. Solenoid valves can be supplied without electric coils as HD5-ES-*-0000 and coils can be supplied separately as B05-***C.

Directly from D.C. supply			
Voltage	Valve Code	Coil Code	Nominal Current (A)
V 12 DC	HD5-ES-*-012C	B05-012C	3,17
V 24 DC	HD5-ES-*-024C	B05-024C	1,73




Permissible supply voltage variation : +5% -10%
Special voltages available : V 48 DC, V 106 DC, V 205 DC

9 SOLENOID COILS, WITH STANDARD ELECTRIC CONNECTION TO ISO 4400 / DIN 43650, FOR AC SUPPLY

Valves type HD5-ES-* can be operated from A.C. supply by the use of coils that incorporate a full wave bridge rectifier. Coils with rectifier can be supplied separately as B05-***A.

Directly from A.C. supply			
Voltage	Valve Code	Coil Code	Nominal Current (A)
V 115 AC / 50 (60) Hz	HD5-ES-*-115A	B05-115A	0,40
V 230 AC / 50 (60) Hz	HD5-ES-*-230A	B05-230A	0,20



Permissible supply voltage variation : +5% -10%
Special voltages available : V 48 DC, V 106 DC, V 205 DC

40003

V2-19

www.aidro.it

Oplysninger indsamlet i dette tekniske dokument har en informativ karakter og kan ændres uden forudgående varsel. Hydra Comp AS accepterer ikke nogen form for ansvar i form af uhensigtsmæssig brug af produkt, undtaget dem, der er relateret til fabriktionsfejl.