


LED-LEJE, VEDLIGEHOLDELSSESFRI
 MAINTENANCE FREE RADIAL BALL-JOINT

GE..ET-2RS



Varenr. Code	d	D	B	C	α	FC (kN)	kg
GE15ET-2RS	15	26	12	9	8	25	0,03
GE17ET-2RS	17	30	14	10	10	32	0,04
GE20ET-2RS	20	35	16	12	9	45	0,07
GE25ET-2RS	25	42	20	16	7	85	0,12
GE30ET-2RS	30	47	22	18	6	110	0,15
GE35ET-2RS	35	55	25	20	6	140	0,23
GE40ET-2RS	40	62	28	22	7	175	0,31
GE45ET-2RS	45	68	32	25	7	225	0,43
GE50ET-2RS	50	75	35	28	6	275	0,55
GE55ET-2RS	55	85	40	32	7	355	0,94
GE60ET-2RS	60	90	44	36	6	430	1,04
GE70ET-2RS	70	105	49	40	6	550	1,55
GE80ET-2RS	80	120	55	45	6	705	2,31
GE90ET-2RS	90	130	60	50	5	860	2,75
GE100ET-2RS	100	150	70	55	7	1070	4,45
GE110ET-2RS	110	160	70	55	6	1150	4,82
GE120ET-2RS	120	180	85	70	6	1680	8,05

FC = MAX DYNAMIC LOAD (Kn)

KUGLE - COUPLING : HÅRD CHROM/PTFE - HARDCHROME /PTFE

MATERIALE : DIN ISO 12240-1 SERIE E

MATERIAL : DIN ISO 12240-1 SERIES E