



H

TRYK AKKUMULATOR
DIAPHRAM HYDROPNEUMATIC ACCUMULATOR



H990R - H3000R

Varenr. Code	Type	P MAX bar	Nitrogen	H	ØD	E	B	C	Q MAX l/min	F	kg
ACH0000100	H 100 R	250	lt 0.15	142	70	45	15	23	40	M18x1.5	1.20
ACH0000350	H 350 R	250	lt 0.35	190	70	35	15	23	35	M18x1.5	1.70
ACH0000500	H 500 R	250	lt 0.45	167	92	55	17	23	50	M18x1.5	1.90
ACH0000700	H 700 R	250	lt 0.70	220	92	40	17	23	40	M18x1.5	2.70
ACH0000990	H 990 R	250	lt 0.99	251	92	-	-	23	50	M18x1.5	3.40
ACH0001000	H 1000 R	250	lt 1.00	200	115	60	19	23	50	M18x1.5	3.50
ACH0001400	H 1400 R	250	lt 1.40	270	115	60	19	23	40	M18x1.5	4.90
ACH0002000	H 2000 R	250	lt 2.00	350	115	60	19	23	40	M18x1.5	5.80
ACH0003000	H 3000 R	250	lt 2.80	400	115	-	-	23	60	1/2" BSP	8.00
ACH0004000	H 4000 R	210	lt 3.80	320	170	95	15	23	80	3/4" BSP	14.00

Temperatur C° - Temperature C° : -20°C - +80°C

MATERIALE - MATERIAL :

HUS - BODY : STÅL - STEEL MEMBRAN - DIAPHRAGM : NBR